

PA-26

Multifunctional Cabinet



The PA-26 delivers HiFi sound in a robust housing, finished with tough structural paint. Whether mobile use or installation – this loudspeaker impresses with its clear and defined reproduction. The PA-26 is equipped with two 6" mid-bass drivers and a 1" HF-driver from European production. The rotatable horn offers a beam angle of 90° x 60°.

Integrated passive filtering allows use without a DSP amplifier - an advantage in cost-sensitive applications. The PA-26 delivers a maximum spl of 126 dB between 85 Hz and 18 kHz – for many applications, a separate subwoofer is not needed. Maximum linearity and operational reliability are achieved through the use of optional DSPs and RMS limiters. The subtle look integrates unobtrusively into any environment.

Two M6 threaded inserts on the back allow for easy installation of a K&M wall bracket while additional M10 inserts on all four sides can be used to attach U-brackets, ceiling mounts, half-couplers, or 35 mm adapters for tripod use.

Clever: The PA-26 has a monitor angle of 45° on one side of the housing but can also be used lying flat on its side as a near-fill. In these positions, the Neutrik NL4 sockets on the narrow sides allow clean and simple cable routing, without plugs and cables protruding to the rear. When used on a tripod or pole, the cable is connected at the bottom; when mounted on a wall or ceiling, it can also be connected at the top.



Special colours (RAL) can be implemented and allow even better visual integration or adaptation to your corporate design. Together with the PA-10B and PA-12B bass extensions, frequency response can be extended below 40 Hz.

By the way: We were able to win over the VARIUS workshops in Grevenbroich for cabinet production and final assembly, thereby also promoting the integration of people with disabilities into the working world.

Technical Specifications

Design	2x 6" + 1"	Bass reflex design
Impedance	16 Ohms (nominal)	
Power Handling	200 / 400 / 800 W	AES / program / peak 10 ms
Sensitivity	96 dB	1 W / 1 m
Max SPL	120 / 126 dB	cont. / peak above 120 Hz
Frequency Response	85 Hz – 18 kHz	-6 dB
Dispersion	90° x 60°	Rotatable horn
Crossover	80 Hz HPF BW18	Mandatory for operation under full power!
Connectors	2x Neutrik NL4	Optional: permanently attached cable (I)
Dimensions	499 x 202 x 230 mm	H x W x D
Weight	6.5 kg	
Colour	black / white (W) as standard	RAL colours on request
Rigging	2x M6, 4x M10 mounting points	

Proper Audio. Solutions - handmade in Germany.

Proper Audio GmbH
Grevenbroicher Str. 8
41363 Jüchen
Germany

www.proper-audio.de
sales@proper-audio.de
+49 (0)2181 - 495300