

PA-3

Full Range Cabinet



The PA-3 gives precision audio in a robust cabinet with a tough structural paint finish. PA-3 feels at home in both mobile and installation applications. This cabinet will amaze you with its clarity and definition. PA-3 is designed with a small footprint, best suited for commercial installation projects that require highest audio quality with minimal visual impact. It is equipped with a 3" full range driver and offers 70° conical dispersion. The internal passive filter network ensures a usable frequency response of 125 Hz through 18 kHz and a maximum SPL of 112 dB (peak) without the need for additional processing (HPF recommended). Use of optional DSP processing and RMS limiters allow for even smoother frequency and phase response as well as high reliability even at full power.

The discreet and 'retro' look makes the PA-3 fit any style of décor. Custom colours are available to make the appearance even more seamless with the surroundings.



Mounting options include integrated M6 fixing points (two per side) for use with the included U-bracket or optional mic stand and mini spigot adapter that will allow using readily available 3/8" hardware. The rear connector plate offers 2x Neutrik NL4 connectors fitted as standard. When mounting to a wall or ceiling, the cable can be fed through the middle (10,5 mm) hole in the bracket, allowing neat and tidy cable management. We also included an integrated source selector switch to allow switching between two sources fed through a single four-conductor cable.

Use in conjunction with PA-8B or PA-12B subwoofers to extend the usable frequency range to below 40 Hz.

By the way: We were able to win over the VARIUS workshops in Grevenbroich for cabinet production and final assembly, thereby also promoting the integration of people with disabilities into the working world.

Technical Specifications

Design	1x 3" mid/high cabinet	Closed box
Impedance	16 or 4 Ohms (nominal)	Please specify when ordering!
Power Handling	30 / 60 / 120 W	AES / program / peak 10 ms
Sensitivity	91 dB	1 W / 1 m
Max SPL	106 / 112 dB	cont. / peak
Frequency Response	125 Hz – 18 kHz	-6 dB
Dispersion	70° conical	
Active Crossover	125 Hz HPF BW18	Mandatory for operation under full power!
Connectors	2x Neutrik NL4	Rear panel selector switch
Dimensions	122 x 122 x 130 mm	H x W x D without cradle and screws
Weight	1.5 kg	
Colour	black / white as standard	RAL colours on request
Rigging	U-bracket (standard)	4x M6 mounting points

Proper Audio. Solutions - handmade in Germany.

Proper Audio GmbH
Grevenbroicher Str. 8
41363 Jüchen
Germany

www.proper-audio.de
sales@proper-audio.de
+49 (0)2181 - 495300

